




(11.7 m - 15.0 m) - 20.0 m - 22.0 m - 24.0 m - 26.0 m

		m/kg																							
m	max. kg	10,0	11,0	12,0	13,0	14,0	15,0	16,0	17,0	18,0	19,0	20,0	21,0	22,0	23,0	24,0	25,5	26,0	27,0	28,0	29,0	30,0	31,0	32,0	33,0
33,0	3,3 - 17,06 2000	2000	2000	2000	2000	2000	2000	2000	2000	1870	1750	1640	1540	1450	1370	1300	1200	1170	1110	1060	1010	1000	1000	1000	1000
30,0	3,3 - 18,10 2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	1880	1770	1660	1560	1480	1400	1300	1270	1210	1200	1200	1200			
25,5	3,3 - 19,19 2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	2000	1900	1790	1690	1600	1550	1550								

		m/kg																							
m	max. kg	10,0	11,0	12,0	13,0	14,0	15,0	16,0	17,0	18,0	19,0	20,0	21,0	22,0	23,0	24,0	25,5	26,0	27,0	28,0	29,0	30,0	31,0	32,0	33,0
33,0	3,3 - 9,91 4000	3950	3490	3120	2820	2570	2350	2170	2010	2000	2000	1890	1780	1680	1590	1510	1400	1360	1300	1240	1180	1130	1090	1040	1000
30,0	3,3 - 10,46 4000	4000	3750	3350	3030	2760	2530	2400	2400	2280	2130	2000	1880	1780	1680	1590	1510	1440	1370	1310	1250	1200			
25,5	3,3 - 11,04 4000	4000	4000	3600	3250	3100	2990	2760	2560	2390	2230	2100	1970	1860	1760	1670	1550								

Technische Daten		Details techniques	
<b>Konstruktionsgewicht</b> Poids de la grue	9'700 kg	<b>Spindelabstand</b> Ecartement	3.8 m
<b>Gegengewicht</b> Contrepoids	18'980 kg	<b>Anschluss</b> Câble d'alimentation	4 x 10 mm <sup>2</sup>
<b>Drehradius</b> Rayon de giration	2.5 m	<b>Ges. elektr. Leistung</b> Puissance total	18.1 Kw
<b>Max. Eckdruck</b> Pression max. par galot	239 kN	<b>Absicherung</b> Fusible:	40 A

 Motor [kW]      11.0 m/min.            6.0 - 50.0	 Motor [kW]      2.3 m/min.            20 / 40	 Motor [kW]      2.2 r.p.m.              0 - 0.9 m <sup>-1</sup>
--	--	--