




m	m / kg	m / kg																
		10,0	11,0	12,0	13,0	14,0	15,0	16,0	17,0	18,0	19,0	20,0	21,0	22,0	23,0	24,0	25,0	26,0
26,0	2,2 - 12,0 2500	2500	2500	2500	2280	2090	1930	1790	1660	1560	1460	1370	1300	1230	1160	1100	1050	1000
24,0	2,2 - 12,4 2500	2500	2500	2500	2370	2180	2010	1860	1730	1620	1520	1430	1350	1280	1210	1150		
12,0	2,2 - 12,0 2500	2500																

Technische Daten		Details techniques	
Konstruktionsgewicht Poids de la grue	9'100 kg	Spindelabstand Ecartement	3,8m x 3,8m
Gegengewicht Contrepoids	11'210 kg	Anschluss Câble d'alimentation	4 x 6 mm ²
Drehradius Rayon de giration	2 m	Ges. elektr. Leistung Puissance total	18.1 Kw
Max. Eckdruck Pression max. par galot	147 kN	Absicherung Fusible:	40 A ohne FI

 Motor [kW] m/min.	11.0 4.0 - 50.0	 Motor [kW] m/min.	2.8 18 / 36	 Motor [kW] r.p.m.	1,5 0 - 0.8 m ⁻¹
--	--------------------	--	----------------	--	--------------------------------